

HD PTZ Camera WLS-EB Series



Features:

- Integrated structure design, flexible deployment, built-in antenna, easy to use
- 4G dual-mode network access wireless network video binding transmission, downward compatible with 3G network
- The infrared night vision supports distance of more than 60 meters, which can realize day and night monitoring
- local support dual TF card storage, single card support $\geq 64g$
- One button anti touch switch, supporting brightness display
- The built-in WiFi module supports WiFi hotspot direct connection to smart phones and tablet preview video
- The device supports built-in lithium battery and can work at full load for more than 6 hours
- The horizontal rotation is 360 degrees and the vertical rotation is 180 degrees
- The protection level is IP66
- The GPS / BeiDou dual mode positioning function
- support smartphone monitoring and tablet PC monitoring and viewing
- The professional portable safety box is convenient to carry,

WLS-EB Specification		
Item	WLS-EB	
System	Main Server	DSP
	Operate System	LINUX
Output	Video	1080P, H.264/265
	Voice	Support talkback, ADPCM, G711
PTZ	Angle	Pan: 360° Tilt: -20°~90°
	Preset	200 sets with 4-line cruise
Internet	Interface	RJ45
	Support	WIFI/Blue tooth/Mobile/GPS/Beidou
	Protocol	TCP/IP,HTTP,DHCP,DN,RTP/RTCP,RTSP,PPPOE
Storage	TF Card	MAX 128G * 2
Environment	Protection	IP66
	Working Temperature	-20°C~60°C
Power	Battery	10AH rechargeable battery for 6hrs work
	Consumption	DC12V, 15W
Parameter	Dimensions	160*238(H)
	Weight	3.3kg