

## Under Water PTZ Camera WLS-UE Series

### Features:

The rotating base underwater camera is mainly used for underwater long-term fixed-point jewelry monitoring. It can rotate horizontally at 0-260 degrees, transmit high-definition video remotely and observe in real time.

**Rotation observation:** 270 ° large viewing angle rotation observation.

**HD Video:** 1080p underwater HD video.

**Auxiliary lighting:** deep water auxiliary lighting.

**Continuous observation:** long time underwater fixed-point observation.



WLS-UE Specification		
Category	Title	WLS-UE50
General	Consumption	50W
	Power	20VDC~36VDC
Camera	Depth	50m
	Sensor	Sony 1/2.8' CMOS
	Image Output	1920*1080 HD
	FOV	75°*50° (Under Water)
	Lens	2.8mm
	Material	316L Stainless Steel
	Cable Length	15m (Up to 75m optional)
	Cable Weight	4.2KG/100m
	Adaptor	24V 30W
	Size	≤ Φ65×100mm
	Weight	≤ 1kg
	Connection	RJ45 or Frank
LED	Illumination	≤ 1000Lux
	Size	≤ Φ65×100mm
	Weight	≤ 1kg
PTZ	Angel	0~360° (Horizon)
	Material	POM Black
	Size	≤ Φ130×130mm
	Weight	1.1kg in air and 0.2kg in water
Cleaner (Optional)	Weight	≤ 1.5kg
	Size	≤ Φ44×220mm
	Angel	140°
	Clear Range	R30~95mm